



EASY CHARGER

Highlights

- 01 Dimensions (H x W x D): 210*160*126
- 02 Simple electrical installation.
- 03 Earth Leakage Protection: 6mA DC+ 30mA AC leakage detection is already in the charger, no Type B RCD required.
- 04 Compatible with 10mm² and 6mm² power wire.
- 05 Wi-Fi connection: you can watch and setup the charger via Wi-Fi.
- 06 The electrical lock, the standard required and is safe for your using.
- 07 Costumed color, the shell can be colored various color.
- 08 Universal socket.
- 09 Power Ratings: it can be adjust via Wi-Fi or DIP switch.



Technical parameter

Rated Power	7 kW (Adjustable)
Rated Voltage	230 VAC (Single Phase)
LV Distribution	TN and IT power system
Voltage Range	230 VAC±20%
Rated Frequency	50Hz/60Hz
Frequency Range	50 Hz±1%
Rated Current	32A (Adjustable)
Charging Mode	Mode 3 , Case B
Dimensions (W x L x H)	160×210×126 mm
Model Order Code	EC-07/B
Effective	>99%
Standby Power Consumption	< 5W
Noise	≤45dB
IP Degree	IP54
IK Degree	IK08
Earth Leakage Protection	Type B
Ambient Temperature	-25~50°C
Operating Humidity	5%~98%
Standards	IEC 61851-1, IEC 61851-22, IEC 62196-2
Connector standard	TYPE 2 Socket meet IEC 62196-1 and IEC 62196-2
Certificate	CE by TUV Rheinland